



## SPECIFICATION SHEET

### Nitrile Rubber - 70° shore A

Unit 21 Priory Industrial Park  
Airspeed Road  
Christchurch  
Dorset  
BH23 4HD

Tel: 01425 278011 / 0845 257 2531  
Fax: 01425 278012 / 0845 257 2532

[www.deltarubber.co.uk](http://www.deltarubber.co.uk)  
[deltasales@deltarubber.co.uk](mailto:deltasales@deltarubber.co.uk)

#### Technical Information

Material:	Nitrile Rubber
Application:	Mild Chemicals / Oil-based products / General purpose
Colour:	Black
Compound:	NBR 70
Density [specific gravity]:	1.45
Hardness [Degrees Shore A]:	70° ± 5°
Tensile Strength [Mpa]:	5.0
Elongation at break %:	250 %
Minimum Temperature :	-20°C
Maximum temperature:	+90°C
Abrasion resistance (mm <sup>3</sup> ):	N/A
Tear resistance (kg/cm):	N/A
Compression Set 70°, 22hrs:	35%



Certificate No: GB08/75575

All recommendations and information contained in this specification sheet are to the best of our knowledge correct. Since conditions of service are beyond our control, users must satisfy themselves that the products are suitable for the intended use. No warranty is implied or given in respect of the information. In any event our liability is limited to the invoice value of the goods delivered to you.